



167 Greenfield Road · Lancaster, PA 17601
Main (717) 336-5575 · Fax (717) 945-1002

www.kalaswire.com

Specification Sheet

Part Number: 690179.04.001 **Revision:** 00 **Date:** August 9, 2013

Description: TR 8/1 10/2 12/4 TRAILER

Conductor:
Gauge: 8
Strand Qty: 19
Strand diameter: 0.0281"
Type: Bare Copper

Separator: None

Insulation:
Type: XLP
Wall: 0.037"
Diameter: 0.208" Tolerance + 0.004"
Tolerance - 0.004"

Conductor:
Gauge: 10
Strand Qty: 19
Strand diameter: 0.0223"
Type: Bare Copper

Separator: None

Insulation:
Type: XLP
Wall: 0.031"
Diameter: 0.176" Tolerance + 0.003"
Tolerance - 0.003"

Conductor:
Gauge: 12
Strand Qty: 19
Strand diameter: 0.0177"
Type: Bare Copper

Separator: None

Insulation:
Type: XLP
Wall: 0.026"
Diameter: 0.142" Tolerance + 0.003"
Tolerance - 0.003"

Color/Sequence: 8 White (CENTER), 12 Brown, 12 Yellow, 10 Red, 10 Lt Blue, 12 Black, 12 Dk Green

Filler: Poly

Separator: Mylar

Jacketing:
Type: PVC
Color: Black
Wall: 0.050"
Overall Diameter: 0.640" Tolerance + 0.010"
Tolerance - 0.010"

Approvals: SAE (Inners only)

RoHS compliant
European Directive 2002/95/EC: Yes, (Jacket and Inners)

Print Legend: SAE^^GXL

Max Voltage Rating: 60 volts DC

Product weight: 315 lb./1000'

Packaging: 1,500' on 32X16X13" Reel