

Specification C5313

US North Central

5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date: 8/3/2013

Issue: 1

Construction

Description:	2 Cond 14(19) GPT/PVC Ag-Cable	Diam. (In)
Component:	2 Conductors	•
Conductor:	14 19/27 BC 2,0mm2 to ASTM B 8-77	0.071"
Insulation:	0.021" Premium Grade PVC	0.113"
Color Code:		
	Color Color Color Color Color Color	
	1 Black 2 Red	1
Cable Assembly:	2 Conductors Bunched Cabled	0.226"
Fillers	Fibrillated Polypropylene for roundness	0.226"
Jacket:	0.035" Black PVC Vehicle/Equipment Grade	0.299"
Jacket Color:	Black	0.299"
Print: No	Print	
Specifications:		
	Black PVC Jacket oil, moisture, UV, flame resistant	
	Temperature Range -40℃ to +105	

Environmental Compliance

EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.