

THERM-O-LINK INC.

10531 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: **IEWC**

TOL Spec ID: **3/C- 1037**
Spec Revision Level: **A1**
Customer Part Number: **TRC1603-0-09/19/69**

Description: **(3) Conductor Round Cable with 3 / 16 Ga GXL, 125C
Inners and 85C PVC Jacket with Print**

Inners: **GXL-16-19-B (BLK/WHT) / GXL-16-19-B (RED/WHT)
/ GXL-16-19-B (BRN/WHT)**

XLPE 125 Deg C Insulated Inners
Stranding: 19 x .0113” Bare lay = 1.25”
Insulation OD = .098”(min) / .101”(nom)

Outer Jacket: PVC 85 Deg C Compound
(Pressure Extruded)

Jacket Color: Black
Cable Lay: 3.0 inches
Jacket Wall Thick(Min): 0.025 inches
Jacket Wall Thick (Nom): 0.030 inches
Jacket Max OD : 0.292 inches
Jacket Min OD : 0.282 inches
Fillers : None
Separator : One 1” White Paper
Surface Print: SAE-GXL

Specification Reference Data

SAE: J-1128 (Rev Dec, 2015)	Ford: N/A	Chrysler: N/A
UL : N/A	CSA: N/A	Packard: N/A
Other: N/A		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: **Mir Hussain (Corporate Product Engineering Manager)**

Date: 8-6-2018