KALAS
Commitment Backed by Capability

167 Greenfield Road · Lancaster, PA 17601
Main (717) 336–5575 · Fax (717) 945-1002 www.kalaswire.com

Specification Sheet

Part Number: 690154.33.001 **Revision:** 01 **Date:** July 29, 2013
Description: TR 16/12 19B 3520373-R1 MULTI-COND

Conductor:
Gauge: 16
Strand Qty: 19
Strand diameter: 0.0112"
Type: Bare Copper

Separator: None

Insulation:
Type: XLP
Color/Sequence: Dk Blue/White & Yellow/White Pair, Purple/White, Lt Green/White & Lt Blue/White Triplex, Gray/White & Orange/White Pair, Lt Blue Single, Black/White, Red/White Brown/White Triplex, Brown Single
Wall: 0.023"
Diameter: 0.103" Tolerance + 0.003" Tolerance - 0.003"

Filler: Paper

Separator: Mylar

Jacketing:
Type: PVC
Color: Black
Wall: 0.090"
Overall Diameter: 0.700" Tolerance + 0.010" Tolerance - 0.010"

Approvals: SAE (Inners only)

RoHS compliant
European Directive 2002/95/EC: Yes, (Jacket and Inners)

Print Legend: SAE^^^GXL

Max Voltage Rating: 60 volts DC

Product weight: 248 lb./1000'

Packaging: 1,250' on 32X16X13" Reel

KALAS