Casters (add 3-7/8" to overall cabinet height)

| 5W	5WR	5WL	5WLR	CBS-5	CBS-5R
set of 4 commercial grade casters	set of 4 fine floor casters	set of 4 commercial grade locking casters	set of 4 fine floor locking casters	skirted base with 4 commercial grade non-locking casters, fits 20" depth models; CBS-5-26 fits 26" depth models	skirted base with 4 fine floor non-locking casters, fits 20" depth models; CBS-5-26R fits 26" depth models

Accessories

SH-5A

c UL us LISTED

zero space full depth front and rear mount SH Series rackshelf, see pg. 157

Trim Panels

Part #	Description
5-BAVTRIM	black brushed & anodized

top and bottom trim panels available to match the finish of the products mounted within the enclosures, includes 2 pieces

Adustable "Split" Rear Rackrail

- Facilitates rear hanging of equipment
- Permits panels to be "mid-mounted"
- All brackets, rails and hardware included
- Cable chase kit required when using this option with ganged enclosures
- Works with steel side panels only; will not accommodate wood side panels

5AR37 installed on **5-37**

Top Fan & RAP Kit

Part #	CFM
5-FAN-K	114

includes 2 fans, 4 grilles, & vent blocker

Bottom Runner Kit

Part #	Fits
5-RS20	20" deep models
5-RS26	26" deep models

low-friction bottom runners allow the Slim 5 to easily slide in and out of credenzas and lecterns

Top and side panels are constructed from thermolaminated MDF. Call for custom top when using cable chase.

WUSS and SH Series shelves need to be installed prior to installation of wood side panels, which conveniently lift off.

Removable Steel Side Panels are vented top and bottom with recessed lift handles and internal locking clips.

Finished in a durable black textured powder coat, each side panel adds 5/8" per side to overall enclosure width.

Doors are capable of being installed with a right or left swing and are equipped with a cam keylock and attractive flush handle.

Requires the use of a cable chase when used in multi-bay installations. Doors provide 1-1/2" clearance.

Rear access panels feature a unique no-hinge "tip-out lift-off" design with a two 4" fan laser knockout for cable pass-through on the bottom.

Securing keylock included.

Part #	Solid Front Door	Plexi Front Door	Steel Side Panels, Pair	Thermolaminate Top/Side Panels**	Rear Access Panel	Adjustable "Split" Rear Rackrail	Cable Chase 3" Wide*
5-8	DO-5-8	DOP-5-8	SP-5-8	–	RAP8	5AR8	5CC8
5-14	DO-5-14	DOP-5-14	SP-5-14	TSP-5-14xx	RAP14	5AR14	5CC14
5-21	DO-5-21	DOP-5-21	SP-5-21	TSP-5-21xx	RAP21	5AR21	5CC21
5-29	DO-5-29	DOP-5-29	SP-5-29	TSP-5-29xx	RAP29	5AR29	5CC29
5-37	DO-5-37	DOP-5-37	SP-5-37	TSP-5-37xx	RAP37	5AR37	5CC37
5-43	DO-5-43	DOP-5-43	SP-5-43	TSP-5-43xx	RAP43	5AR43	5CC43
5-8-26	DO-5-8	DOP-5-8	SP-5-8-26	–	RAP8	5AR8-26	5CC8-26
5-14-26	DO-5-14	DOP-5-14	SP-5-14-26	TSP-5-14-26xx	RAP14	5AR14-26	5CC14-26
5-21-26	DO-5-21	DOP-5-21	SP-5-21-26	TSP-5-21-26xx	RAP21	5AR21-26	5CC21-26
5-29-26	DO-5-29	DOP-5-29	SP-5-29-26	TSP-5-29-26xx	RAP29	5AR29-26	5CC29-26
5-37-26	DO-5-37	DOP-5-37	SP-5-37-26	TSP-5-37-26xx	RAP37	5AR37-26	5CC37-26
5-43-26	DO-5-43	DOP-5-43	SP-5-43-26	TSP-5-43-26xx	RAP43	5AR43-26	5CC43-26

*Custom width cable chases available, please call for details. ***Replace 'xx' with DS = Darkstone, GS = Graystone, PS = Pepperstone (Tops Only), SL = Slate (Sides Only)
SG = Shark Gray, EA = Ebony Ash, WG = Wenge, DC = Dark Cherry, DP = Dark Pecan, AG = Aged Cherry, HM = Honey Maple, LW = Light Walnut, MP = Maple.
See pg. 175 for thermolaminate finish options.