

INSULATE  
SEAL  
PROTECT

6:1  
SHRINK RATIO



## HIGH RATIO, FLAME RETARDANT CROSS-LINKED POLYOLEFIN TUBING

HIGH RATIO HEAT SHRINK TUBING ACCOMMODATES EXTREME DIFFERENCES BETWEEN CABLES, CONNECTORS AND BACKSHELLS

### FEATURES AND BENEFITS

- Up to 6:1 shrink ratio
- Flame retardant
- Accommodates a wide variety of connector shapes and configurations
- Available in semi-rigid or flexible material
- Optional thermoplastic adhesive liner for complete environmental protection and insulation
- Available in 25 ft reels
- Continuous operating temperature: -55°C to 110°C
- Shrink temperature: 120°C

### STANDARDS

- Meets material properties of SAE- AMS- DTL 23053/15

### TYPICAL APPLICATIONS

- Wire harnesses
- Abrasion and impact resistance
- Strain relief and protection of cables and connectors




## CFHR DIMENSIONS - SEMI-RIGID

ORDER NUMBER	EXPANDED		RECOVERED				LENGTHS	
	INTERNAL DIAMETER (MIN) D		INTERNAL DIAMETER (MAX) d		WALL THICKNESS (MIN) W			
	MM	IN	MM	IN	MM	IN	M	IN
0750	19.0	0.75	3.2	0.125	3.2	0.123	1.2	48
1300*	33.0	1.30	5.5	0.220	3.4	0.135	1.2	48
1750	44.4	1.75	7.4	0.290	3.6	0.140	1.2	48
2000	50.8	2.00	8.3	0.330	4.3	0.170	1.2	48
2750	69.8	2.75	11.7	0.460	4.8	0.190	1.2	48
3500	88.9	3.50	17.1	0.673	4.3	0.170	1.2	48
4700	119.4	4.70	22.9	0.900	4.8	0.190	1.2	48

## CFHR-FR DIMENSIONS

1250	31.8	1.25	5.6	0.220	1.5	0.060	1.2	48
1750	44.4	1.75	8.0	0.315	2.4	0.095	1.2	48
2500	63.5	2.50	12.7	0.500	3.0	0.120	1.2	48
3000	81.3	3.20	19.1	0.750	3.6	0.140	1.2	48



## ORDERING

- Select a dimension which will shrink snugly over the component to be covered. If recovery is restricted the resulting wall thickness will be less than specified.
- Select Options:
  - Printing: Printed or Unprinted
  - Adhesive Lining: Lined (D) or Unlined (U)
  - Lengths: 6, 12 or 48 inches, or 25 ft spools (unlined only)
- Please specify the product name, order reference number and options you require.
- Order Example: CFHR, 0750, black, unprinted, unlined, 25 ft lengths

Please contact your Customer Service Representative for information on custom colours, sizes, lengths and material data sheet.