

## TT100OUTSM



**Article Number:** 556-00169

**Thermal Transfer Ribbon, 4.33" X 242', .50" Core, 100 Resin, Black, 1/EA**



Download spec sheet

### Base Data

**Local Order Number** TT100OUTSM

**Type** TT100OUTSM

**Color** Black (BK)

**Features and Benefits**

- Ribbons are resin based for the best print durability.
- Ribbons are available to fit all HellermannTyton printers for easy resupply.
- Ribbons are available in colors for maximizing design printing capabilities.
- Ribbons meet UL recognition and Military standard where applicable to meet specific industry label requirements.

**Product Description** HellermannTyton thermal transfer ribbons are designed for use in HellermannTyton thermal transfer printers. Available on 1/2" and 1" cores, the ribbons are coated side out and available in two different lengths. All ribbons are available in a variety of colors and are matched to the HellermannTyton label stock to give the best chemical and abrasion resistance.

**Variant** Coloured ribbon

**Short Description** Thermal Transfer Ribbon, 4.33" X242', .50" Core, 100 Resin, Black, 1/EA

### Product Dimensions

**Length L (Imperial)** 242.0 ft

**Length L (Metric)** 74.0 m

**Width W (Imperial)** 4.33 "

**Width W (Metric)** 110.0 mm

**Print Method** Thermal Transfer

**Recommended Material** 100, 250, 336, 409, 795, 799, 822, POX, ShrinkTrak

### Logistics and Packaging

**Quantity Per** pieces

**Package Quantity (Imperial)** 1

**Package Quantity (Metric)** 1

**Carton Quantity** 1

**Dimensions calculated (WxHxD) metric** 110.0 mm x

**Reel Length (metric)** 74 m

**Reel Length (imperial)** 242.0 ft

**Weight (Metric)** 0.15 kg

**Weight (imperial)** 0.662 lbs

### Material and Specifications

**Material** Polyester Film

**Material Shortcut** PET  
**Operating Temperature** +40°F to +300°F (+4°C to +82°C)  
**ROHS compliant (Article 4 - 1)** Yes  
**Certification/Specification** UL-Recognized