

TT822OUTSM



Article Number: 556-00145

Thermal Transfer Ribbon, 4.33" X 299', .50" Core, 822 Resin, Black, 1/EA



Download spec sheet

Base Data

Local Order Number TT822OUTSM

Type TT822OUTSM

Color Black (BK)

- Features and Benefits**
- Ribbons are resin based for the best print durability.
 - Ribbons are available to fit all HellermannTyton printers for easy resupply.
 - Ribbons are available in colors for maximizing design printing capabilities.
 - Ribbons meet UL recognition and Military standard where applicable to meet specific industry label requirements.

Product Description HellermannTyton thermal transfer ribbons are designed for use in HellermannTyton thermal transfer printers. Available on 1/2" and 1" cores, the ribbons are coated side out and available in two different lengths. All ribbons are available in a variety of colors and are matched to the HellermannTyton label stock to give the best chemical and abrasion resistance.

Variant Coloured ribbon

Short Description Thermal Transfer Ribbon, 4.33" X299', .50" Core, 822 Resin, Black, 1/EA

Product Dimensions

Length L (Imperial) 242.0 ft

Length L (Metric) 74.0 m

Width W (Imperial) 4.33 "

Width W (Metric) 110.0 mm

Print Method Thermal Transfer

Recommended Material 100/250/336/822/822C/795/799

Logistics and Packaging

Quantity Per EA

Package Quantity (Imperial) 1

Package Quantity (Metric) 1

Carton Quantity 1

Dimensions calculated (WxHxD) metric 110.0 mm x

Labels per Column 1

Reel Length (imperial) 242.0 ft

Reel Length (metric) 74 m

Material and Specifications

Material Type 822, Polyester, black (BK)

Material Shortcut 822

Operating Temperature +40°F to +300°F (+4°C to +82°C)
ROHS compliant (Article 4 - 1) Yes
Certification/Specification UL-Recognized