

## TT822OUT



**Article Number:** 556-00101

**Thermal Transfer Ribbon, 4.33" X 984', 1" Core, 822 Resin, Black, 1/EA**



Download spec sheet

### Base Data

**Local Order Number** TT822OUT

**Type** TT822OUT 110MM

**Color** Black (BK)

- Features and Benefits**
- Ribbons are resin based for the best print durability.
  - Ribbons are available to fit all HellermannTyton printers for easy resupply.
  - Ribbons are available in colors for maximizing design printing capabilities.
  - Ribbons meet UL recognition and Military standard where applicable to meet specific industry label requirements.

**Product Description** HellermannTyton thermal transfer ribbons are designed for use in HellermannTyton thermal transfer printers. Available on 1/2" and 1" cores, the ribbons are coated side out and available in two different lengths. All ribbons are available in a variety of colors and are matched to the HellermannTyton label stock to give the best chemical and abrasion resistance.

**Variant** Coloured ribbon

**Short Description** Thermal Transfer Ribbon, 4.33" X 984', 1" Core, 822 Resin, Black, 1/EA

### Product Dimensions

**Length L (Imperial)** 984.0 ft

**Length L (Metric)** 300.0 m

**Width W (Imperial)** 4.33 "

**Width W (Metric)** 110.0 mm

**Print Method** Thermal Transfer

**Recommended Material** 100/250/336/822/822C/795/799

### Logistics and Packaging

**Quantity Per** pieces

**Package Quantity (Imperial)** 1

**Package Quantity (Metric)** 300 m

**Carton Quantity** 24

**Dimensions calculated (WxHxD) metric** 110.0 mm x

**Reel Length (metric)** 300 m

**Reel Length (imperial)** 984.0 ft

**Weight (Metric)** 0.1 kg

**Weight (imperial)** 0.662 lbs

### Material and Specifications

**Material** Type 822, Polyester, black (BK)

**Material Shortcut** 822

**Operating Temperature** +40°F to +104°F (+4°C to +40°C)

**ROHS compliant (Article 4 - 1)** Yes

**Certification/Specification** UL-Recognized