



ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire Corporation
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

**#24 7/32 BARE COPPER .016" PVC
SAE J1128 TYPE TWP 105C**

CONDUCTOR:	#24 7/32 BARE COPPER 3/4" CONCENTRIC NOMINAL O.D. .024" APPROXIMATE CIRCULAR MILL AREA 442 WEIGHT PER THOUSAND FEET 1.40# BASIC SPECIFICATION ASTM B 8 ASTM B 286
PVC:	TEMPERATURE RATING 105c VOLTAGE RATING 300 VOLTS WALL THICKNESS .016" ELONGATION 330% AVERAGE TENSILE STRENGTH 2450 PSI AVERAGE SPECIFIC GRAVITY 1.32 DUROMETER (SHORE) 91 (A) OXYGEN INDEX 28 BRITTLE POINT -24c SPARK TESTED 7,100 VOLTS FINISHED O.D. .056 WEIGHT PER THOUSAND FEET 2.60#
PRINT:	NOT REQUIRED – UNPRINTED

info@atlaswirecorp.com

Revision date 04/29/11