

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: TXL-10-1004

Description: 10 GA THINWALL XLPE 125 DEG C, 104 STRANDS
TINNED

Conductor (Stranding): 104 x 30 AWG Tinned Copper Lay = 1.5", Auto

Conductor OD (Nom) 0.121 inches

Max. Lay Length: 1.5 inch Lay

Nom. Wall Thickness: 0.017 inches

Min Wall Thickness: 0.015 inches

Min O. D: 0.151 inches

Nom. O. D: 0.155 inches

Max . O.D : 0.155 inches

Max Runout: 0.004 inches

Strip Force: 5 (min) - 24 (max)

Circular Mils (CMA): 9343 (Min)

Surface Print: NONE

Specification Reference Data


SAE: J-1128
UL : N/A
Other: N/A

Ford: N/A
CSA: N/A

Chrysler: N/A
Packard: N/A

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By:


Mir Hussain (Corporate Quality Engineer)

Approved By:


Kevin J. Ryan (Corporate Quality Manager)

Date: 1-4-2010