PRODUCT SPECIFICATION

DATEREVECNDESCRIPTION6/24/2015EADDED LOW TEMP RATING.


Parent Number: F14023-

Description: 14 19/27 BC TXL per J1128 ESB-M1L123-A

MS-8288

DIAMETER: 0.103

TOLERANCE ± : 0.003



Stranding: 19/27 BC LHL

Style: TXL per SAE J 1128, Ford ESB-M1L123-A, Chrysler MS-8288

NOM WALL: 0.016

MINIMUM WALL: 0.013

Insulation: XLPE

Print Legend: NO PRINT

Voltage: Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as " a class designation based on the

retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes: 1. Min. Temp Rating = -40C

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer	Approval	<u>l:</u>

 Southwire

Copperfield[®]

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115