## **PRODUCT SPECIFICATION**

DATE	REV	<b>ECN</b>	DESCRIPTION
4/6/2009	Α	20875	SPECIFICATION CREATED


Parent Number: F20205-

Description: 20 7/28 BC TXL per J1128 ESB-M1L123-A

MS-8288 UTMS-12501(REV.A)

**DIAMETER:** 0.078

 $TOLERANCE \pm : 0.003$ 



Stranding: 7/28 BC LHL

Style: TXL per J1128, ESB-M1L123-A, MS-8288, UTMS-12501(REV.A)

**Insulation:** XLPE

**Print Legend: NO PRINT** 

Voltage: Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as " a class designation based on the

retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

*Notes:* 

This product complies with European Directive 2002/95/EC (RoHS)

**Customer Approval:** 

Customer Part Nbr(s):\_\_\_\_\_

Approved By:\_\_\_\_\_\_Date:\_\_\_\_\_

Title:\_\_\_\_\_Company Name:\_\_\_\_

COLEMAN CABLE, INC

1530 Shields Drive Waukegan, IL 60085

CCI

Phone: 1-800-323-9355 www.colemancable.com