


# COPPERFIELD PRODUCT SPECIFICATION

<i>DATE</i>	<i>REV</i>	<i>ECN</i>	<i>DESCRIPTION</i>
1/17/2006	A	10960	SPECIFICATION CREATED

**CF Parent Number:** 20121-

**Description:** 20 19/32 BC TXL per J1128

**DIAMETER:** 0.070  
**TOLERANCE ±:** 0.003



**Stranding:** 19/32 BC LHL

**Style:** TXL per SAE J 1128

**Insulation:** XLPE

**Print Legend:** NO PRINT

**Voltage:** Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems.

**Temperature:** The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as " a class designation based on the retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

**Notes:**

This product complies with European Directive 2002/95/EC (RoHS)

**Customer Approval:**

**Customer Part Nbr(s):** \_\_\_\_\_

**Approved By:** \_\_\_\_\_ **Date:** \_\_\_\_\_

**Title:** \_\_\_\_\_ **Company Name:** \_\_\_\_\_

**COPPERFIELD, LLC.**

1115 W. North Street  
Bremen, IN 46506

Phone: 574-546-5115

Fax: 574-546-5995

www.copperfieldllc.com



Copperfield