

TYPE ABRH NEW



This CSA-certified, non-jacketed flexible aluminum conduit has many universal wiring applications.

CONSTRUCTION:

Type ABRH is formed from a heavy-gauge aluminum strip. Its profile and helical shape allow it to withstand substantial impact and crushing forces.

Meets Federal Specification A-A-55810 Type I

APPLICATION:


This conduit is intended as a metal raceway for wires and cable where CSA certification is required. Suitable for use with connectors intended for FMC (Flexible Metal Conduit).

RoHS and WEEE Compliant.

Certified File #LL18858 Conforms to CSA 22.2 No. 56 for use per the Canadian Electrical Code C22.1 Section 12-1000

METAL USED: Aluminum

Types ABRH Strip Profile



TYPE FSC NEW



This non-UL, non-jacketed flexible steel conduit has many universal wiring applications

CONSTRUCTION:


Type FSC is formed from a corrosion resistant hot-dipped galvanized steel. Its profile and helical shape allow it to withstand substantial impact and crushing forces

APPLICATION:

This conduit as a metal raceway for wire and cable where UL Listing is not required. Suitable for use with connectors intended for FMC (Flexible Metal Conduit).

METAL USED: Steel

Types FSC Strip Profile



Trade Size (In.)	Type	Diameter (In.)		Inside Bend Radius (In.)	Weight (Lbs.)/100 Ft.	Coil Footage (Ft.)		Reel Footage (Ft.)	
		Inner Min/Max	Outer Min/Max			Length	Part #	Length	Part #
ABRH									
3/8	ABRH-10	0.375/0.393	0.560/0.610	2	7	100	ABRH-69701	500/1000	ABRH-69703/69704
7/16	ABRH-716	0.437/0.457	-/0.675	2.25	8	100	ABRH-69707	500/1000	ABRH-69708/69709
1/2	ABRH-11	0.625/0.645	0.860/0.920	3	16	100	ABRH-69711	500/1000	ABRH-69713/69714
3/4	ABRH-12	0.812/0.835	1.045/1.105	4	18	100	ABRH-69722	500/1000	ABRH-69723/69724
1	ABRH-13	1.000/1.040	1.300/1.380	5	35	50	ABRH-69732	400	ABRH-69734
1-1/4	ABRH-14	1.250/1.300	1.550/1.630	6.2	43	50	ABRH-69742	400	ABRH-69744
1-1/2	ABRH-15	1.500/1.575	1.850/1.950	7.5	55	25	ABRH-69752	100	ABRH-69753
2	ABRH-16	2.000/2.080	2.350/2.454	10	73	25	ABRH-69762	-	-
2-1/2	ABRH-17	2.500/2.700	2.860/3.060	12.5	90	25	ABRH-69772	-	-
3	ABRH-18	3.000/3.200	3.360/3.560	15	107	25	ABRH-69782	-	-
4	ABRH-19	4.000/-	4.360/4.560	20	142	25	ABRH-69792	-	-
FSC									
3/8	FSC-10	0.375/0.393	0.560/0.610	2	13	100	69501	1000	69504
1/2	FSC-11	0.625/0.645	0.860/0.920	3	19	100	69511	1000	69514
3/4	FSC-12	0.812/0.835	1.045/1.105	4	25	100	69522	500/1000	69523/69524
1	FSC-13	1.000/1.040	1.300/1.380	5	28	50	69532	-	-
1-1/4	FSC-14	1.250/1.300	1.550/1.630	6.2	38	50	69542	-	-
1-1/2	FSC-15	1.500/1.575	1.850/1.950	7.5	48	25	69552	-	-
2	FSC-16	2.000/2.080	2.350/2.454	10	100	25	69562	-	-
2-1/2	FSC-17	2.500/2.700	2.860/3.060	12.5	166	25	69572	-	-
3	FSC-18	3.000/3.200	3.360/3.560	15	190	25	69582	-	-
3-1/2	FSC-350	3.500/-	3.860/4.060	17.5	170	25	69587	-	-
4	FSC-19	4.000/-	4.360/4.560	20	200	25	69592	-	-