

# PFA - Type 10362 (AWM)

Teflon® High Temperature Lead Wire

UL: 250°C, 600V

CSA: 250°C, 600V, AWM I A/B, FT1



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
10362/24	24	19/36	0.010	0.3	0.044	1.1	2	3
10362/22	22	19/34	0.010	0.3	0.050	1.3	3	4
10362/20	20	19/32	0.010	0.3	0.055	1.4	5	7
10362/18	18	19/30	0.010	0.3	0.064	1.6	7	10
10362/16	16	19/.0117	0.010	0.3	0.076	1.9	10	15
10362/14	14	19/.0147	0.010	0.3	0.089	2.3	15	22
10362/12	12	19/.0185	0.010	0.3	0.109	2.8	23	34
10362/10	10	19/.0234	0.010	0.3	0.137	3.5	36	54
10362/08	8	133/29	0.030	0.8	0.222	5.6	69	103
10362/06	6	133/27	0.030	0.8	0.263	6.7	102	152
10362/04	4	133/25	0.030	0.8	0.316	8.0	155	231
10362/02	2	133/23	0.030	0.8	0.390	9.9	242	360
10362/01	1	259/25	0.045	1.1	0.462	11.7	313	466
10362/1/0	1/0	259/24	0.045	1.1	0.511	13.0	406	604
10362/2/0	2/0	259/23	0.045	1.1	0.567	14.4	491	731
10362/3/0	3/0	259/22	0.045	1.1	0.607	15.4	611	909
10362/4/0	4/0	259/21	0.045	1.1	0.690	17.5	756	1125

Teflon is a registered trademark of DuPont Corporation

## Notes

- Soft-annealed, nickel-plated copper conductor
- Perfluoroalkoxy (PFA) insulation
- A variety of insulation colors available

## Applications

For use in electronic and appliance applications. Rated for continuous use up to 250°C.