

FEP - Type 1332 (AWM)

Teflon® High Temperature Lead Wire

UL: 200°C, 300V

CSA: 180°C, 300V, AWM I A/B, FT1



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
1332/26	26	7/34	0.015	0.4	0.049	1.2	2	3
		19/38	0.015	0.4	0.049	1.2	2	3
1332/24	24	7/32	0.015	0.4	0.054	1.4	3	5
		19/36	0.015	0.4	0.053	1.3	3	5
1332/22	22	7/30	0.015	0.4	0.060	1.5	4	6
		19/34	0.015	0.4	0.062	1.6	4	6
1332/20	20	7/28	0.015	0.4	0.068	1.7	6	9
		19/32	0.015	0.4	0.070	1.8	6	9
1332/18	18	7/26	0.015	0.4	0.077	2.0	8	12
		19/30	0.015	0.4	0.081	2.1	9	13
1332/16	16	7/24	0.015	0.4	0.088	2.2	11	16
		19/.0117	0.015	0.4	0.086	2.2	11	16
1332/14	14	7/22	0.015	0.4	0.101	2.6	17	25
		19/.0147	0.015	0.4	0.115	2.9	17	25
1332/12	12	19/.0186	0.015	0.4	0.134	3.4	26	39
1332/10	10	37/26	0.015	0.4	0.156	4.0	26	39

Teflon is a registered trademark of DuPont Corporation

Notes

- Soft-annealed, tinned copper conductor
- Fluorinated ethylene polypropylene (FEP) insulation
- A variety of insulation colors available

Alternative Constructions

- Soft-annealed, nickel-plated copper conductor
- Soft-annealed, silver-plated copper conductor

Available Certifications

UL: 1333

Applications

For use in electronic and appliance applications. Rated for continuous use up to 200°C.