

# PFA - Type 1726 (AWM)

Teflon® High Temperature Lead Wire

UL: 250°C, 300V

CSA: 250°C, 300V, AWM I A/B, FT1



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>1726/24</b>	24	19/36	0.013	0.3	0.053	1.3	3	5
<b>1726/22</b>	22	19/34	0.013	0.3	0.060	1.5	4	6
<b>1726/20</b>	20	19/32	0.013	0.3	0.068	1.7	6	8
<b>1726/18</b>	18	19/30	0.013	0.3	0.079	2.0	9	13
<b>1726/16</b>	16	19/29	0.013	0.3	0.086	2.2	11	16
<b>1726/14</b>	14	19/27	0.013	0.3	0.098	2.5	16	23

Teflon is a registered trademark of DuPont Corporation

### Notes

- Soft-annealed, nickel-plated copper conductor
- Perfluoroalkoxy (PFA) insulation
- A variety of insulation colors

### Alternative Constructions

- M series Perfluoroalkoxy copolymer (MFA) insulation

### Applications

For use in electronic and appliance applications. Rated for continuous use up to 250°C.