

# PFA - Type 1911 25KV

Teflon® High Temperature / High Voltage Lead Wire

UL: 250°C, 25KV



IEWC Part Number	AWG	Stranding	Nominal O.D.		Approx. Weight	
			in	mm	lbs/1k ft	kg/km
1911/24	24	7/32	0.078	2.0	5	8
1911/22	22	7/30	0.084	2.1	7	10
1911/20	20	7/28	0.090	2.3	8	12
1911/18	18	19/30	0.098	2.5	11	16
		19/29	0.110	2.8	15	22
1911/16	16	26/30	0.110	2.8	15	22
		41/30	0.126	3.2	21	31
1911/14	14	41/30	0.126	3.2	21	31
1911/12	12	65/30	0.144	3.7	30	44

Teflon is a registered trademark of DuPont Corporation

## Notes

- Soft-annealed, nickel-plated copper conductor
- Extruded perfluoroalkoxy copolymer (PFA) insulation
- A variety of insulation colors available

## Alternative Constructions

- Heavier insulation, 30kV voltage rating
- Polytetrafluoroethylene (PTFE) insulation
- M series Perfluoroalkoxy copolymer (MFA) insulation

## Applications

For use in manufacturing and oven & furnace applications. Rated for continuous use up to 250°C.