

# Silicone - Type 3239 40kV (TV)

High Voltage Hook-up Wire

UL: 150°C, 40kV

CSA: 150°C, 40kV



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>3239/24T07S40</b>	24	7	0.122	3.1	0.268	6.8	31	46
<b>3239/22T07S40</b>	22	7	0.122	3.1	0.273	6.9	32	48
<b>3239/20T10S40</b>	20	10	0.122	3.1	0.283	7.2	36	54
<b>3239/18T16S40</b>	18	16	0.122	3.1	0.289	7.3	39	58
<b>3239/16T26S40</b>	16	26	0.122	3.1	0.301	7.6	44	65
<b>3239/14T41S40</b>	14	41	0.122	3.1	0.316	8.0	52	77
<b>3239/12T65S40</b>	12	65	0.122	3.1	0.331	8.4	62	92
<b>3239/10T105S40</b>	10	105	0.122	3.1	0.354	9.0	79	118

## Notes

- Soft-annealed, tinned copper conductor
- Extruded silicone rubber insulation
- RoHS Compliant
- Standard insulation colors: white, black and red

## Applications

For use in electronic and appliance applications. Rated for continuous use up to 150°C.