

EPDM - Type 3340/3374 (CL1254)

Motor Lead Wire

UL: 125°C, 150°C Non-flexing, 600V

125°C, 150°C Non-flexing, 600V



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
3340/18	18	16/30	0.045	1.1	0.142	3.6	13	19
3340/16	16	26/30	0.045	1.1	0.154	3.9	18	27
3340/14	14	41/30	0.045	1.1	0.169	4.3	23	34
3340/12	12	65/30	0.045	1.1	0.190	4.8	33	49
3340/10	10	65/28	0.060	1.5	0.240	6.1	52	77
		104/30	0.060	1.5	0.250	6.4	52	77
3340/08	8	84/27	0.080	2.0	0.327	8.3	95	141
		133/29	0.080	2.0	0.345	8.8	95	141
3340/06	6	84/25	0.080	2.0	0.383	9.7	135	201
		133/27	0.080	2.0	0.385	9.8	135	201
3340/04	4	105/24	0.080	2.0	0.432	11.0	187	278
		133/.0177	0.080	2.0	0.445	11.3	187	278
3340/03	3	133/24	0.080	2.0	0.453	11.5	225	335
3340/02	2	163/24	0.080	2.0	0.494	12.5	280	417
		259/26	0.080	2.0	0.500	12.7	280	417
3340/01	1	210/24	0.095	2.4	0.583	14.8	410	610
		259/25	0.095	2.4	0.585	14.9	410	610
3340/1/0	1/0	259/24	0.095	2.4	0.620	15.7	441	656
		262/24	0.095	2.4	0.633	16.1	441	656
3340/2/0	2/0	259/23	0.095	2.4	0.660	16.8	552	821
		504/26	0.095	2.4	0.698	17.7	552	821
3340/3/0	3/0	259/22	0.095	2.4	0.730	18.5	692	1,030
		630/26	0.095	2.4	0.758	19.3	692	1,030
3340/4/0	4/0	266/.0286	0.095	2.4	0.790	20.1	819	1,219
		805/26	0.095	2.4	0.849	21.6	796	1,185

Notes

- Soft-annealed, tinned copper conductor
- Ethylene propylene diene monomer (EPDM) insulation
- Standard insulation colors: black and red

Available Certifications

CSA: FT2

Applications

For use in electric motor & generator, heating & cooling and appliance applications. Rated for continuous use up to 125°C in flexing and 150°C in non-flexing applications.