

## Portable Power Cable 90°C UL C(UL) MSHA Mining Grade



### SPECIFICATIONS & STANDARDS

ICEA S-75-381/NEMA WC58, ICEA S-95-658/NEMA WC70, ASTM B 172, ASTM B 33

### CONSTRUCTION:

- Conductors:** Flexible strand tin copper, ASTM B 172 and ICEA S-75-381
- Separator:** Tape separator between the conductor and insulation
- Insulation:** Ethylene-propylene rubber (EPR), ICEA S-75-381 sec 3.15, table 3-12
- Grounding cond:** Tin copper, ICEA S-75-381, table 3-12
- Ground check:** Yellow Polypropylene-Insulation tin copper conductor, ICEA S-75-381 table 3-21
- Assembly:** *Sizes 4/0 and smaller:* Three power, ground check and two polyester (green mylar) taped grounding conductors cabled together; Nylon open braid applied overall. *Sizes 250 MCM and larger:* Three power, ground check and two polyester (green mylar) taped grounding conductors cabled together to form round core; Single faced rubber filled binder tape applied overall
- Jacket:** Black extra heavy duty, integral-filled CPE thermoset compound, ICEA S-75-381 sec 3.21, table 3-3
- Color Code:** ICEA S-75-381 sec 3.18; black, white, red

FEATURES	APPLICATION
<ul style="list-style-type: none"> <li>- Excellent flexibility</li> <li>- Highly ozone, sun, weather and flame resistant</li> <li>- Rated and flexible at -40°C</li> <li>- Excellent impact and abrasion resistant</li> <li>- Special construction for reeling and trailing</li> <li>- Oil and heat resistant</li> <li>- Indent printed for easy identification</li> </ul>	<ul style="list-style-type: none"> <li>- For use as trailing mining cable.</li> <li>- Use on AC off track equipment such as miners, shuttle cars, cutting machines loading machines and drills as well as conveyors and pumps</li> <li>- Supply power to open pit strip and deep mines</li> <li>- For applications requiring ground check conductor for added safety.</li> </ul>

### APPROVALS:

- UL:** E207132 – Oil Resistant; Oil Resistant Inners; Sunlight Resistant; 90C Wet or Dry
- C(UL):** E207132 - FT1; FT5; -40°C +90°C
- MSHA:** P-7K-268101

### 3 CONDUCTOR

Part Number	Power Conductor Size	Power Conductor Stranding	Size		Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal O.D.		Approx. Weight		Ampacity (1) 30°C Ambient Temp.
			Ground	Ground Check			inches	mm	lbs/1000 ft	kgs/km	
GGC2-3MNG	2 AWG	259 7x37	7	10	0.060	0.165	1.34	34.0	1461	2176	152
GGC1-3MNG	1 AWG	259 7x37	6	8	0.080	0.170	1.51	38.4	1861	2772	177
GGC1/0-3MNG	1/0 AWG	266 19x14	5	8	0.080	0.170	1.65	41.9	2256	3360	205
GGC2/0-3MNG	2/0 AWG	342 19x18	4	8	0.080	0.190	1.75	44.5	2695	4014	237
GGC4/0-3MNG	4/0 AWG	532 19x28	2	8	0.080	0.205	2.04	51.8	3889	5791	316
GGC350-3MNG	350 MCM	888 37x24	1/0	6	0.095	0.280	2.68	68.1	6482	9652	433

(1) Ampacity - Free air measured. Based on continuous duty at 90°C conductor temperature per 2011 NEC Table 400.5(A)(2)

### STANDARD PRINT LEGEND:

TF CABLE (SIZE) TYPE G-GC PORTABLE POWER CABLE 2000V 90C SUN RES OIL RES 90C WET OR DRY (UL) E207132 C(UL) FT1 FT5 (-40C) P-7K-268101-MSHA

### SPECIAL FACTORY OPTIONS:

- Jacket:** Other colors available
- MSHA:** P-7K-268077 (Neoprene)
- CSA:** 1523058 (LR 103932) - FT1; FT5; 90°C; (-40°C) (Neoprene)
- Jacket:** TPU Other colors available
- MSHA:** P-07-KA030001 (TPU)