

Portable Power Cable 90°C UL C(UL) MSHA Industrial Grade



SPECIFICATIONS & STANDARDS

ICEA S-75-381/NEMA WC58, ICEA S-95-658/NEMA WC70, ASTM B172, ASTM B 33, UL 44

CONSTRUCTION:

Conductors:	Flexible strand tin copper, ASTM B-172 and ICEA S-75-381/NEMA WC58
Separator:	Tape separator between conductor and insulation
Insulation:	Ethylene-propylene rubber (EPR), ICEA S-75-381 sec 3.15, table 3-16
Assembly:	Conductors and rubber fillers cabled to form round core
Reinforcement:	Single faced rubber filled binder tape over insulation
Jacket:	Black heavy duty CPE thermoset compound, ICEA S-75-381 sec 3.4, table 3-4
Color Code:	ICEA S-75-381 sec 3.18; black, white, red, green, orange

FEATURES	APPLICATIONS
<ul style="list-style-type: none"> - Excellent flexibility - Water resistant and flame resistant - Rated and flexible at -40°C to +90°C - Excellent impact and abrasion resistant - Ozone sunlight oil, grease, weather, chemical resistant 	<ul style="list-style-type: none"> - Portable power systems - Other industrial applications - Mining application where bare grounding conductors are not required

APPROVALS:

UL:	E207132 – Oil Resistant; Oil Resistant Inners; Sunlight Resistant; 90C Wet or Dry
C(UL):	E207132 - FT1; FT5; -40°C +90°C
MSHA:	P-7K-268101

5 CONDUCTOR

Part Number	Power Conductor Size	Power Conductor Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight		Ampacity (1) 30°C Ambient Temp.
			inches	mm	inches	mm	lbs/1000 ft	kgs/km	A
W8-5	8 AWG	133 7x19	0.06	1.52	1.07	27.2	776	1154	52
W6-5	6 AWG	259 7x37	0.06	1.52	1.24	31.5	1024	1524	69
W4-5	4 AWG	259 7x37	0.06	1.52	1.36	35.2	1432	2131	91
W2-5	2 AWG	259 7x37	0.06	1.52	1.56	39.8	2051	3052	121
W1-5	1 AWG	259 7x37	0.06	1.52	1.85	47.1	2665	3967	141
W1/0-5	1/0 AWG	266 19x14	0.08	2.03	1.98	50.4	3406	5069	164
W2/0-5	2/0 AWG	342 19x18	0.08	2.03	2.13	54.1	3596	5351	189
W3/0-5	3/0 AWG	418 19x22	0.08	2.03	2.27	57.6	4728	7035	219
W4/0-5	4/0 AWG	532 19x28	0.08	2.03	2.46	62.6	5512	8203	252

6 CONDUCTOR

Part Number	Power Conductor Size	Power Conductor Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight		Ampacity (1) 30°C Ambient Temp.
			inches	mm	inches	mm	lbs/1000 ft	kgs/km	A
W6-6	6 AWG	259 7x37	0.06	1.52	1.30	33.0	1272	1891	69

(1) Ampacity - Free air measured. Based on continuous duty at 90°C conductor temperature per 2011 NEC Table 400.5(A)(2). Green conductor for grounding purpose only.

STANDARD PRINT LEGEND:

TF CABLE (SIZE) TYPE W PORTABLE POWER CABLE 2000V 90C SUN RES OIL RES 90C WET OR DRY (UL) E207132 C(UL) FT1 FT5 (-40°C) P-7K-268101-MSHA

SPECIAL FACTORY OPTIONS:

Jacket:	Other colors available
MSHA:	P-7K-268077 (Neoprene)
CSA:	1523058 (LR 103932) – FT1; FT5; 90C; (-40C) (Neoprene)