



PRODUCT INFORMATION SHEET

UL - GXL Copper Primary Wire
Recreational Vehicle Cable - SAE Types
125°C - General Purpose (GXL) - Cross Linked Polyolefin Insulated

Features

Copper Conductors per ASTM B3 (Bare Copper) & ASTM B33 (Tinned Copper)
Insulation Material: Crosslinked Polyolefin
RoHS Compliant

Compliance

SAE: J1128 GXL
UL File E465737

Applications

Low tension cables for -40°C to 125°C
Low voltage ≤ 60 V DC
Temperature -40°C to 125°C

Product Options

Colors available upon request
Packaging Options: Drums and Reels, various sizes and disposal or recyclable

Conductor Size	Number of Strands	Conductor Area, Minimum	Insulation Thickness, Nominal	Insulation Thickness, Minimum	Cable OD, Maximum
ga	#	cmils	mm	mm	mm
20	7	1 072	0.58	0.41	2.40
18	16	1537	0.58	0.41	2.50
16	19	2 336	0.58	0.41	2.90
14	19	3 702	0.58	0.41	3.20
12	19	5 833	0.66	0.46	3.80
10	19	9 343	0.79	0.55	4.70
8	19	14 810	0.94	0.66	6.00

Rev 0 (2022-10-31)

Written by: KMorrow