

ETFE (Tefzel® 750) - Type 10109 (AWM)

Tefzel® Hook-up Wire

UL: 200°C, 300V

CSA: 200°C, 300V, AWM I A/B, FT1



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
10109/24	24	7/32	0.006	0.2	0.036	0.9	2	3
10109/22	22	7/30	0.006	0.2	0.042	1.1	2	3
10109/20	20	7/28	0.006	0.2	0.050	1.3	4	6
10109/18	18	7/26	0.006	0.2	0.060	1.5	6	9
10109/16	16	7/.0192	0.008	0.2	0.074	1.9	9	13
10109/14	14	7/.0242	0.008	0.2	0.088	2.2	14	21
10109/12	12	19/.0186	0.010	0.3	0.109	2.8	22	33

Tefzel® is a registered trademark of DuPont Corporation

Notes

- Soft-annealed, nickel-plated copper conductor
- Modified ethylene tetrafluoroethylene (ETFE) insulation
- A variety of insulation colors available

Alternative Constructions

- Soft-annealed, tinned copper conductor
- Soft-annealed, silver-plated copper conductor

Applications

For use in electronic and appliance applications. Rated for continuous use up to 200°C.