

# mPPE (EcoWire™) - Type 11028 (AWM)

Non-PVC Environmentally Friendly Hook-Up Wire

UL: -40°C up to 105°C, 600V, VW-1

CSA: -40°C up to 105°C, 600V, AWM I A/B



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
11028/28	28	7/36	0.010	0.3	0.034	0.9	2	2
11028/26	26	7/34	0.010	0.3	0.038	1.0	2	3
11028/24	24	7/32	0.010	0.3	0.043	1.1	2	3
11028/22	22	7/30	0.010	0.3	0.049	1.2	3	4
11028/20	20	10/30	0.010	0.3	0.055	1.4	5	7
11028/18	18	Solid	0.010	0.3	0.059	1.5	8	11
11028/18	18	16/30	0.010	0.3	0.067	1.7	8	11
11028/16	16	26/30	0.011	0.3	0.081	2.1	12	18
11028/14	14	Solid	0.011	0.3	0.086	2.2	16	24
11028/14	14	41/30	0.011	0.3	0.096	2.4	16	24
11028/12	12	65/30	0.012	0.3	0.117	3.0	25	37
11028/10	10	105/30	0.012	0.3	0.142	3.6	38	57

EcoWire™ is a trademark of Alpha Wire

## Notes

- Soft-annealed, tinned copper conductor
- Noryl modified polyphenylene ether (mPPE) insulation
- RoHS Compliant
- A variety of insulation colors available

## Applications

For use in automotive, electronic and appliance applications. Rated for continuous use from -40°C up to 105°C.