


CONSTRUCTION			ELECTRICAL CHARACTERISTICS	
CONDUCTOR	AWG	26 AWG	RATING: TEMP. 60°C VOLTAGE: 150V	
	MATERIAL	BARE COPPER	CONDUCTOR RESISTANCE: AT 20°C MAX	
	COND. SIZE	7/0.160mm	26AWG: 148.94Ω/km	
	COND. DIAMETER	0.48mm	INSULATION RESISTANCE: 45.3MΩ/km MIN. at 20°C	
INSULATION	MIN. AVG. THICK	0.15mm	DIELECTRIC STRENGTH: AC 500V/MINUTE	
	AVERAGE THICK	0.18mm		
	MATERIAL	PP		
	O.D.	0.95±0.05mm		
JACKET	N.O.	4C		
	MIN. ACG. THICK	0.725mm		
	COLOR	BLACK		
	O.D.	2.5±0.1 x 5.0±0.2mm		

COLOR CODE	
1C	YELLOW
2C	GREEN
3C	RED
4C	BLACK

 SHAXON INDUSTRIES
4950 EAST HUNTER AVE.
ANAHEIM, CA. 92807

DESCRIPTION: FLAT CABLE: 26AWGx4C, STRANDED BARE COPPER, BLACK		CHK:	APRVD:	REV.:	DWG BY: Catherine
COLOR: SEE TABLE	THIS DRAWING IS THE EXCLUSIVE PROPERTY OF SHAXON INDUSTRIES, INC. ITS ACCEPTANCE CONSTITUTES AN AGREEMENT THAT SHOULD BE TREATED AS A STRICTLY CONFIDENTIAL DOCUMENT TO BE USED FOR NO OTHER PURPOSE THAN TO AID IN THE ASSEMBLY OR OPERATION OF UNITS FURNISHED BY OR FOR SHAXON IND. INC. OR OTHERWISE AS EXPRESSLY AUTHORIZED IN WRITING BY SHAXON IND. INC. THAT IT IS RETURNED UPON REQUEST AND IS NOT TO BE COMMUNICATED, DISCLOSED OR COPIED EXCEPT AS EXPRESSLY AUTHORIZED IN WRITING BY SHAXON INDUSTRIES INC. AutoCAD Release 12 c1a, Serial #: 110-10626948	DATE: 11/06/2008		DO NOT SCALE	
MATERIAL: SEE TABLE		PART NO.:		UL300-4BK	
DWG NO. C.A.					