

EPDM - Type 3284 (AWM, CL1254)

Motor Lead and Internal Appliance Wire

UL: 125°C, 600V

CSA: 125°C, 600V, AWM I A/B, FT2



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
3284/18	18	16/30	0.045	1.1	0.138	3.5	10	15
3284/16	16	26/30	0.045	1.1	0.154	3.9	14	21
3284/14	14	41/30	0.045	1.1	0.169	4.3	20	30
3284/12	12	65/30	0.045	1.1	0.188	4.8	29	43
3284/10	10	105/30	0.060	1.5	0.241	6.1	54	80
3284/08	8	133/29	0.080	2.0	0.330	8.4	75	112
3284/06	6	133/27	0.080	2.0	0.380	9.7	114	170
3284/04	4	133/25	0.080	2.0	0.446	11.3	168	250
3284/02	2	266/26	0.080	2.0	0.496	12.6	261	388
3284/01	1	817/30	0.095	2.4	0.564	14.3	348	518
3284/1/0	1/0	1045/30	0.095	2.4	0.610	15.5	423	629
3284/2/0	2/0	1330/30	0.095	2.4	0.667	16.9	522	777
3284/3/0	3/0	1672/30	0.095	2.4	0.714	18.1	642	955
3284/4/0	4/0	2109/30	0.095	2.4	0.790	20.1	792	1,178

Notes

- Soft-annealed, tinned copper conductor
- Ethylene propylene diene monomer (EPDM) insulation
- Standard insulation colors: black and red

Applications

For use in electric motor & generator and appliance applications. Rated for continuous use up to 125°C.