

UL Style 3284

Appliance Wiring

125°C - 600 volts AC- Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
 Insulation: 125°C EPDM
 RoHS and REACH Compliant

Compliances

CSA CL-1254
 Voltage Rating 600 volts AC
 Horizontal Flame per UL 1581
 UL 758

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors for base and stripe combinations
 Packaging options: reels, drums, returnable containers

Applications

Internal Wiring of appliances

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
18	16	30	0.048	0.138	0.041	13	5
16	26	30	0.060	0.154	0.041	18	8
14	41	30	0.074	0.169	0.041	24	13
12	65	30	0.086	0.188	0.041	33	20
10	105	30	0.115	0.241	0.054	54	33
8	133	29	0.162	0.330	0.054	91	53
6	133	27	0.205	0.380	0.054	133	86
4	133	25	0.249	0.446	0.054	200	133
2	266	26	0.320	0.491	0.054	270	202
1	817	30	0.368	0.564	0.070	355	258
1/0	1045	30	0.399	0.610	0.070	421	323
2/0	1330	30	0.464	0.667	0.086	524	411
3/0	1672	30	0.515	0.714	0.070	633	516
4/0	2109	30	0.565	0.790	0.070	798	653

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com

