



PRODUCT INFORMATION SHEET

UL Style 3614

125 deg c, No flexing for 150 deg C, 1000 Vac, horizontal flame

AWG size	Number of Strands	Area of Cross Section, min (mm ²)	Conductor	Insulation material	Min Wall (mm)	Nom Wall (mm)	Diameter, Reference Only (mm)	Separator	Print Legend	Referenced Part Number
8ga	133	8.19	Tinned Copper	125°C/150°C EPDM	1.37	1.52	6.53	physical	8 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	14934910IE
6ga	133	13.0	Tinned Copper	125°C/150°C EPDM	1.37	1.52	7.34	physical	6 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	149350-10IE
4ga	133	20.7	Tinned Copper	125°C/150°C EPDM	1.37	1.52	8.54	physical	4 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	145795-81IE
2ga	266	32.9	Tinned Copper	125°C/150°C EPDM	1.37	1.52	10.84	physical	2 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	145794-81IE
1ga	817	41.5	Tinned Copper	125°C/150°C EPDM	1.83	2.03	13.00	physical	1 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	151350-81IE
1/0	1045	52.4	Tinned Copper	125°C/150°C EPDM	1.83	2.03	13.79	physical	1/0 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	151349-81IE
2/0	1330	66.0	Tinned Copper	125°C/150°C EPDM	1.83	2.03	15.44	physical	2/0 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	148937-81IE
3/0	1672	83.0	Tinned Copper	125°C/150°C EPDM	1.83	2.03	16.74	physical	3/0 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	152060-81IE
4/0	2109	105.0	Tinned Copper	125°C/150°C EPDM	1.83	2.03	18.01	physical	4/0 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C 600V/1000V PRESTOLITE P.G. CSA CL 1503 OR AWM I A/B 125C 600V FT2	145946-81IE

Voltage Rating: 1000 Vac
 Temperature Rating: -40°C to 125°C/150°C
 Specifications: UL: 3614
 CSA: CL-1503 & AWM
 Packaging: Reels
 Other: RoHS compliant

Rev 0 (2020-06-02)

Written by: FBenafield