



APPLIANCE WIRING MATERIAL

Subj.758

Section 1

Page 1110

Issued:1959-05-01

Revised:2014-06-16

Style 1110

Single-conductor cable using Non-Integral Jacket

---

|               |  |
|---------------|--|
| <b>Rating</b> | 105 deg C, 300 Vac or 600 Vdc, Horizontal Flame. |
|---------------|--|

---

|                  |                                     |
|------------------|-------------------------------------|
| <b>Conductor</b> | 26 AWG - 16 AWG, Solid or Stranded. |
|------------------|-------------------------------------|

---

|                            |   |
|----------------------------|---|
| <b>Insulated Conductor</b> | Labeled or complying with manufacturer's AWM procedure, or Extruded PVC, 15 mils minimum average thickness, 13 mils minimum thickness at any point. |
|----------------------------|---|

---

|               |           |
|---------------|-----------|
| <b>Shield</b> | Optional. |
|---------------|-----------|

---

|               |  |
|---------------|--|
| <b>Jacket</b> | Extruded PVC, 15 mils minimum average thickness, 12 mils minimum thickness at any point. |
|---------------|--|

---

|                 |                                   |
|-----------------|-----------------------------------|
| <b>Standard</b> | Appliance Wiring Material UL 758. |
|-----------------|-----------------------------------|

---

|                |          |
|----------------|----------|
| <b>Marking</b> | General. |
|----------------|----------|

---

|            |                  |
|------------|------------------|
| <b>Use</b> | Internal Wiring. |
|------------|------------------|

---

UL and the UL Logo are trademarks of UL LLC © 2017