



APPLIANCE WIRING MATERIAL

Subj.758

Section 1

Page 1571

Issued:1972-12-27

Revised:2015-02-14

Style 1571

Single conductor with extruded insulation

Rating	80 deg C, 30 Vac, Horizontal flame.
---------------	-------------------------------------

Conductor	50 AWG minimum. Solid or stranded.
------------------	------------------------------------

Insulation	Extruded PVC, SRPVC, foamed PVC, foamed SRPVC, XLPVC, XLSRPVC, foamed XLPVC or foamed XLSRPVC, 2 mils minimum thickness at any point, 100 mils maximum thickness.
-------------------	---

Covering	Optional. Extruded PVC, Nylon, ETFE, Polyester, XLPVC, XL Nylon, XLETFE or XL Polyester, 2 mils minimum thickness at any point, or lacquered braid.
-----------------	---

Shield	Optional.
---------------	-----------

Jacket	Optional. Same as covering.
---------------	-----------------------------

Shield	Optional.
---------------	-----------

Covering	Optional. Same as covering.
-----------------	-----------------------------

Standard	Appliance Wiring Material UL 758.
-----------------	-----------------------------------

Marking	General.
----------------	----------

Use	Internal Wiring of Class 2 Circuits in electronic equipment.
------------	--
