



APPLIANCE WIRING MATERIAL

Subj.758

Section 3

Page 3127

Issued:1960-08-25

Revised:2012-03-09

Style 3127

Single conductor cable with extruded insulation

Rating	150 deg C, 600 Vac, Horizontal flame.
---------------	---------------------------------------

Conductor	8 AWG - 2 AWG stranded copper, coated with tin, nickel, or silver; strands 30 AWG, or larger.
------------------	---

Insulation	Extruded SR, 60 mils minimum average thickness, 54 mils minimum thickness at any point.
-------------------	---

Covering	Glass braid, 16 or 24 carriers, 150-1/3 glass: for 8 AWG, 3 ends, 12 picks per in; 6 AWG, 4 ends, 10.5 picks per in; 4 AWG, 4 ends, 12.0 picks per in; 3 AWG, 5 ends, 10.5 picks per in; 2 AWG, 5 ends, 10.5 picks per in. Treatment of Fibrous Covering of Same as for Type SF-2 Fixture Wire.
-----------------	---

Standard	Appliance Wiring Material UL 758.
-----------------	-----------------------------------

Marking	General.
----------------	----------

Use	Leads for hazardous location motors or Internal Wiring of Appliances.
------------	---

UL and the UL Logo are trademarks of UL LLC © 2017