

LARGE FLAT TINNED COPPER

* Denotes QQB575 construction

NOTE: When bare copper is required add (B) to our part #

EXAMPLE - 240B

<u>CCC NO.</u>	<u>NOMINAL FLAT WIDTH</u>	<u>NOMINAL THICKNES</u>	<u>AWG. OF INDIV ENDS</u>	<u>NO. OF STRANDS (CARRIER)</u>	<u>NO. OF WIRES PER STRAND</u>	<u>TOTAL NO OF INDIV. WIRES</u>	<u>APPROX. AWG. EQUIV.</u>	<u>NOMINAL CIRCULAR MILLS</u>	<u>CURRENT CARRYING CAPACITY (AMPS)</u>
240 *	1/2"	0.08	30	24	10	240	6	24000	93
242 *	5/8"	0.085	30	24	15	360	5	36000	120
244	3/4"	0.11	30	24	20	480	3	48000	145
246	7/8"	0.12	30	24	24	576	3	57600	165
248	15/16"	0.13	30	24	26	624	2	62400	170
250	15/16"	0.13	30	24	27	648	2	64800	175
252	1"	0.14	30	24	32	768	1	76800	195
260	3/4"	0.05	30	48	5	240	6	24000	93
262 *	1 3/8"	0.06	30	48	7	336	5	33600	100
264	1"	0.07	30	48	8	384	4	38400	120
266	1 1/4"	0.08	30	48	10	480	3	48000	145
268 *	1 1/2"	0.08	30	48	11	528	3	52800	145
270	7/8"	0.09	30	48	12	576	2	57600	150
272	1 3/8"	0.09	30	48	14	672	2	67200	165
274	1 1/2"	0.1	30	48	16	768	1	76800	180
276	1 5/8"	0.11	30	48	18	864	1	86400	200
278	1 3/8"	0.12	30	48	22	1056	1/0	105600	235
279	1 3/4"	0.13	30	48	26	1248	2/0	124800	250
280	2"	0.13	30	48	28	1344	2/0	134400	255
282	2"	0.14	30	48	32	1536	3/0	153600	290
284	2"	0.15	30	48	35	1680	3/0	168000	320
286	2 3/8"	0.175	30	48	44	2112	4/0	211200	370
287	3"	0.19	30	48	47	2256	4/0	225600	390
288	2 1/2"	0.19	30	48	52	2496	250 MCM	249600	410

Continental Cordage Corporation




INTERNATIONAL WIRE
Continental Cordage
 315-655-9800 phone
 315-655-9686 fax

|

|

|

|



APPROX. SHIPPING WEIGHT LBS.
83
121
170
193
210
225
270
88
129
137
168
192
200
230
265
283
362
430
464
530
570
730
780
900

