

## TINNED COPPER TUBULAR BRAIDS

CCC NO.	NOM. I.D. WHEN ROUNDED	AWG. OF INDIV ENDS	NO. OF STRANDS (CARRIER)	NO. OF WIRES PER STRAND	TOTAL NO OF INDIV. WIRES	APPROX. AWG. EQUIV.	NOMINAL CIRCULAR MILLS	CURRENT CARRYING CAPACITY (AMPS)	APPROX. SHIPPING WEIGHT LBS.
---------	------------------------	--------------------	--------------------------	-------------------------	--------------------------	---------------------	------------------------	----------------------------------	------------------------------

160 *	1/32"	36	24	1	24	22	600	7	5
162 *	1/16"	36	24	2	48	19	1200	11	7
163 *	5/64"	36	24	3	72	18	1800	16	9
164 *	7/64"	36	24	4	96	16	2400	19	11
166 *	1/8"	36	24	5	120	15	3000	25	13
167 *	5/32"	36	24	10	240	12	6000	40	24
<b>168 *</b>	<b>11/64"</b>	<b>36</b>	<b>24</b>	<b>7</b>	<b>168</b>	<b>14</b>	<b>4200</b>	<b>32</b>	<b>17</b>
170 *	13/64"	34	24	8	192	11	7630	46	31
170/1*	13/64"	36	24	13	312	11	7800	46	31
171 *	1/4"	36	24	16	384	10	9600	53	38
171/1*	9/32"	30	24	5	120	9	12060	60	47
171/2*	3/8"	30	24	7	168	8	16880	75	62
172 *	3/8"	36	48	8	384	10	9600	53	40
173 *	7/16"	30	24	10	240	6	24120	90	85
173/1*	1/2"	30	24	15	360	5	36180	120	122
174 *	1/2"	36	48	11	528	9	13200	62	53
175 *	9/16"	30	48	10	480	3	48240	145	156
175/1*	21/32"	30	48	16	768	1	77180	190	259
176 *	25/32"	36	48	18	864	7	21600	88	79
177 *	7/8"	30	48	7	336	5	33770	100	123
178 *	1"	30	48	8	384	4	38600	120	140
179 *	1 1/8"	30	48	9	432	4	43420	130	155
180	1 1/4"	30	48	10	480	3	48240	145	168
181 *	1 3/8"	30	48	11	528	3	53060	145	185
182 *	1 1/2"	30	48	12	576	3	57890	145	200
183 *	2"	30	48	14	672	2	67540	180	230
184	2 1/4"	30	48	16	768	1	77180	190	260

\* Denotes QQB575 and AA59569 constructions

**Continental Cordage Corporation**



**INTERNATIONAL WIRE**  
*Continental Cordage*  
 315-655-9800 phone  
 315-655-9686 fax

