

Specification Sheet

Lake Cable Part #: V162S/16DR-QR

Description: 16 AWG 2 conductor 7 strand bare copper with polyvinylchloride and nylon insulation, an

aluminum/mylar shield with a stranded tinned copper drain wire with an overall PVC jacket 600V control tray cable, PLTC, NPLF & FPL, approved for use in SUN RES DIR BUR OIL RES I 90° C

applications.

1. Conductor

1.1. AWG Size & Stranding: 16 AWG, 7 Strands Class B1.2. Material: Annealed Bare Copper

1.3. Conductor Count: 2 Conductors

2. Insulation

2.1. Material: Polyvinylchloride & Nylon2.2. Wall Thickness: 0.015" PVC & 0.005" Nylon

2.3. Color Code: Method 1, Table E-2

3. Assembly

3.1. Lay Length: 3.00" LHL 3.2. Fillers: N/A 3.3. Binder: N/A

3.4. Shield: Aluminum/Mylar Tape - 100% coverage

3.5. Drain Wire: 16 AWG, 7 Strand Tinned Copper

4. Jacket

4.1. Material: Polyvinylchloride

4.2. Wall Thickness: 0.045"
4.3. Diameter: 0.291"
4.4. Color: Black
4.5. Ripcord: Yes
4.6. Cold Bend Rating: -40°C
4.7. Weight: 55 lbs./Mft.

5. Markings

5.1. Type: Cable shall be permanently identified via surface inkjet print 5.1. Legend: LAKE CABLE E207231 16AWG 2C SHIELDED (UL) NPLF 90'C

150V PVC/N OR PLTC OR FPL OR TC-ER 600V 90'C DRY/WET SUN RES DIR BUR

OIL RES I PVC JACKET FT4 "ROHS II" REACH MADE IN USA

5.2. Footage Markers: Yes

6. Standards

- 6.1. Refer to NEC (NFPA 70) article 336 for installation guidelines
- 6.2. Cable is suitable for use in Class I Division II hazardous locations
- 6.3. UL listed as Type TC-ER per UL Standard 1277 for tray cables and Quad Rated TC-ER, PLTC, NPLF & FPL
- 6.4. UL approved for Direct Burial, Sunlight and Oil I Resistant applications
- 6.5. Meets requirements of PLTC per UL Standard 13 for Power-Limited Circuit Cables
- 6.6. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
- 6.7. Meets ICEA S-73-532, where applicable
- 6.8. All materials used in the manufacture of this cable are RoHS II & REACH compliant
- 6.9. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION