



PW ES-1573
Prestoflex Welding Cable
125°C EPDM

Features

Conductors available in tinned or copper
Insulation: 125°C EPDM
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors
Packaging options: reels

Applications

Cables used for welding electrical

| AWG size | Number of Strands | Strand Size (ga) | Nom Cond OD (in) | Nom OD (in) | Nom. Wall (in) | Min. Wall (in) | Approx. Net Weight (lbs/mft) | Approx. Cu (lbs/mft) |
|----------|-------------------|------------------|------------------|-------------|----------------|----------------|------------------------------|----------------------|
| 6 | 280 | 30 | 0.185 | 0.356 | 0.080 | 0.056 | 127 | 80 |
| 4 | 440 | 30 | 0.237 | 0.403 | 0.080 | 0.056 | 183 | 128 |
| 2 | 704 | 30 | 0.297 | 0.485 | 0.090 | 0.063 | 268 | 192 |
| 1 | 880 | 30 | 0.345 | 0.529 | 0.095 | 0.067 | 340 | 258 |
| 1/0 | 1112 | 30 | 0.380 | 0.591 | 0.105 | 0.074 | 432 | 324 |
| 2/0 | 1408 | 30 | 0.429 | 0.635 | 0.105 | 0.074 | 520 | 409 |
| 3/0 | 1760 | 30 | 0.465 | 0.685 | 0.105 | 0.074 | 646 | 518 |
| 4/0 | 2224 | 30 | 0.544 | 0.764 | 0.115 | 0.081 | 810 | 653 |
| 250MCM | 2368 | 30 | 0.577 | 0.825 | 0.115 | 0.081 | 942 | 764 |

REV:-1- 3/30/2011

Customer Service Group

1 Prestolite Drive
Paragould, Arkansas 72450
Phone: 800-952-3842 870-236-8141
Fax: 870-239-6139
Web: www.prestolitewire.com