



**PW ES-1573**  
**Prestoflex Welding Cable**  
**125°C EPDM**

**Features**

Conductors available in tinned or copper  
Insulation: 125°C EPDM  
RoHS and REACH Compliant

**Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors  
Packaging options: reels

**Applications**

Cables used for welding electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Nom. Wall (in)	Min. Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
6	280	30	0.185	0.356	0.080	0.056	127	80
4	440	30	0.237	0.403	0.080	0.056	183	128
2	704	30	0.297	0.485	0.090	0.063	268	192
1	880	30	0.345	0.529	0.095	0.067	340	258
1/0	1112	30	0.380	0.591	0.105	0.074	432	324
2/0	1408	30	0.429	0.635	0.105	0.074	520	409
3/0	1760	30	0.465	0.685	0.105	0.074	646	518
4/0	2224	30	0.544	0.764	0.115	0.081	810	653
250MCM	2368	30	0.577	0.825	0.115	0.081	942	764

REV:-1- 3/30/2011

**Customer Service Group**

1 Prestolite Drive  
Paragould, Arkansas 72450  
Phone: 800-952-3842 870-236-8141  
Fax: 870-239-6139  
Web: [www.prestolitewire.com](http://www.prestolitewire.com)