

COPPERFIELD PRODUCT SPECIFICATION

| DATE | REV | ECN | DESCRIPTION |
|----------|-----|------|-----------------------|
| 5/4/2005 | A | 8610 | SPECIFICATION CREATED |

EXCELENE® Welding Cable
EPDM Insulated
105°C to -50°C, 600V

| Copperfield Parent Part Number | AWG Size | Conductor Stranding | Nominal O.D. | Nominal Wall | Approx. Lbs./MFT |
|--------------------------------|----------|------------------------|--------------|--------------|------------------|
| 06013- | 6 | 7x38/30 Bare Copper | 0.320 | 0.060 | 116 |
| 04005- | 4 | 7X56/30 Bare Copper | 0.375 | 0.060 | 163 |
| 03001- | 3 | 7x75/30 Bare Copper | 0.428 | 0.060 | 215 |
| 02004- | 2 | 7x92/30 Bare Copper | 0.440 | 0.060 | 251 |
| 01004- | 1 | 7X112/30 Bare Copper | 0.515 | 0.080 | 321 |
| 1/004- | 1/0 | 19x54/30 Bare Copper | 0.550 | 0.080 | 388 |
| 2/004- | 2/0 | 19X66/30 Bare Copper | 0.590 | 0.080 | 474 |
| 3/005- | 3/0 | 19X85/30 Bare Copper | 0.660 | 0.080 | 601 |
| 4/005- | 4/0 | 19x108/30 Bare Copper | 0.725 | 0.080 | 762 |
| 25001- | 250 MCM | 19x129/30 Bare Copper | 0.875 | 0.125 | 1,029 |
| 35003- | 350 MCM | 19X7X26/30 Bare Copper | 0.998 | 0.125 | 1,371 |
| 50001- | 500 MCM | 19X7X37/30 Bare Copper | 1.150 | 0.125 | 1,882 |

Copperfield, LLC

1115 W. Plymouth St.
PO Box 360
Bremen, IN 46506
P: 574-546-5115
F: 574-546-5995
E-mail: copperfield@copperfieldllc.com



ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE
PLEASE CONTACT YOUR CUSTOMER SERVICE REPRESENTATIVE FOR THE LATEST SPECIFICATIONS