



**PW ES-1573**  
**Prestoflex Welding Cable**  
**125°C EPDM**

**Features**

Conductors available in tinned or copper  
Insulation: 125°C EPDM  
RoHS and REACH Compliant

**Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors  
Packaging options: reels

**Applications**

Cables used for welding electrical

| AWG size | Number of Strands | Strand Size (ga) | Nom Cond OD (in) | Nom OD (in) | Nom. Wall (in) | Min. Wall (in) | Approx. Net Weight (lbs/mft) | Approx. Cu (lbs/mft) |
|----------|-------------------|------------------|------------------|-------------|----------------|----------------|------------------------------|----------------------|
| 6        | 280               | 30               | 0.185            | 0.356       | 0.080          | 0.056          | 127                          | 80                   |
| 4        | 440               | 30               | 0.237            | 0.403       | 0.080          | 0.056          | 183                          | 128                  |
| 2        | 704               | 30               | 0.297            | 0.485       | 0.090          | 0.063          | 268                          | 192                  |
| 1        | 880               | 30               | 0.345            | 0.529       | 0.095          | 0.067          | 340                          | 258                  |
| 1/0      | 1112              | 30               | 0.380            | 0.591       | 0.105          | 0.074          | 432                          | 324                  |
| 2/0      | 1408              | 30               | 0.429            | 0.635       | 0.105          | 0.074          | 520                          | 409                  |
| 3/0      | 1760              | 30               | 0.465            | 0.685       | 0.105          | 0.074          | 646                          | 518                  |
| 4/0      | 2224              | 30               | 0.544            | 0.764       | 0.115          | 0.081          | 810                          | 653                  |
| 250MCM   | 2368              | 30               | 0.577            | 0.825       | 0.115          | 0.081          | 942                          | 764                  |

REV:-1- 3/30/2011

**Customer Service Group**

1 Prestolite Drive  
Paragould, Arkansas 72450  
Phone: 800-952-3842 870-236-8141  
Fax: 870-239-6139  
Web: [www.prestolitewire.com](http://www.prestolitewire.com)