

HOOK-UP WIRE

MIL-W-16878/5
 MIL-W-16878/22
 MIL-W-16878/34
 TYPE EE-1000V



Description:

Stranded Silver Plated Copper, Extruded PTFE Insulation.

Characteristics:

Temperature Rating:
 MIL-W-16878: -60°C to +200°C
 UL 1180: +200°C
 Voltage Rating:
 MIL-W-16878: 1000V
 UL 1180: 300V

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
2224	M16878/5BEB-X	24	7/32	.015	.054
2224/19	M16878/5BEE-X	24	19/36	.015	.055
2222	M16878/5BFB-X	22	7/30	.015	.060
2222/19	M16878/5BFE-X	22	19/34	.015	.062
2220	M16878/5BGB-X	20	7/28	.015	.068
2220/19	M16878/5BGE-X	20	19/32	.015	.070
2218/19	M16878/5BHE-X	18	19/30	.015	.080
2216/19	M16878/5BJE-X	16	19/29	.015	.089
2214/19	M16878/5BKE-X	14	19/27	.017	.106

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
2212/19	M16878/5BLE-X	12	19/25	.017	.124
2210	M16878/5BMG-X	10	37/26	.017	.145
2208	M16878/22BNL-X	8	133/29	.020	.210
2206	M16878/22BPL-X	6	133/27	.020	.252
2204	M16878/34BRL-X	4	133/25	.020	.315

NOTE: 2220/19 - 2224 Dual rated to UL 1180

COLORS:

0 - Black, 1 - Brown, 2 - Red
3 - Orange, 4 - Yellow, 5 - Green
6 - Blue, 7 - Violet, 8 - Gray, 9 - White
X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.