



**356**

4Cond Shld/Unshld 22/18AWG CMR  
Audio, Control and Intercom

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-	
Component	Shielded	Unshielded
CONDUCTOR PARAMETER	-	
• Number of Conductors	2	2
• AWG Size	20	18
• Conductor Stranding	7x28	7x26
• Conductor Type	Bare Copper	Bare Copper
• Nominal DCR	10.1 Ohm/1000ft	6.2 Ohm/1000ft
INSULATION PARAMETER	-	
• Insulation Type	Thermoplastic	Thermoplastic
• Insulation Thickness	0.008 in	0.008 in
• Insulation Color Code	1. Black 2.Red	1. White 2.Green
SHIELDING PARAMETER	-	
• Shield Type	Overall 100% Aluminum Foil	None
• Drain Wire Type	Tinned Copper	
• Drain Wire AWG	22 AWG	
ELECTRICAL CHARACTERISTICS	-	
• Nom. Cap. Between Conductors	34 pF/ft	
• Nom. Cap. Conductor to Shield	67 pF/ft	

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	4
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.15 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	42 lbs
Bend Radius	1.349 in
Cable Weight	34 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



**356**

Audio, Control and Intercom

## Related Products

RELATED PRODUCTS