Custom Residential Equipment Mounting Solutions

CORNEL .

TATOR

Who says your

entertainment

equipment

can't look

as elegant

as the rest of

your home?





Whether you choose to install a home theater, distributed music system, or whole-house control, today's advanced audio and video components provide homeowners with more entertainment choices than ever before.

These integrated systems require engineered equipment mounting solutions designed to be built-in, unobtrusive, and highly aesthetic, while providing easy access to equipment connections.

Professionals choose Middle Atlantic Products.

* Installation by Home Systems

Custom Manufactured in 48 hours!

Challenge —	 Mounting high-end and consumer audio and video components in professional equipment racks. The RSH custom fascia system provides secure equipment mounting, and is the professional's choice for trimming non-rackmount components. 	
	RSH Series Custom Rackshelves consist of a shelf and a custom fascia which non-rackmount components perfectly. Available with an anodized or textured finish Chances are the specified component is liste among the over 8,000 measured units in ou comprehensive online database!	NEW design provides enhanced ventilation**
	PART # FINISH	

RSH4A black brushed and anodized RSH4C silver brushed and anodized RSH4S black textured powder coat

-C clamp kit for mobile or seismic installations



Visit <u>middleatlantic.com</u> to see if the specified component is listed using the custom rackshelf search!

NEW rear mount power option now available!

PD-815SC-PBSH

Challenge -

STATE N

Solution -

Installing audio and video equipment where the look of shelving is preferred.

Slide out rotating shelving systems combine the functionality of a professional racking system with the simplicity of adjustable shelves.



Installation by Hom

The NEW REB Series Low Profile Rotating Slide Out Equipment Base is perfect for systems with fewer components.

		RECOMMENDED		USEABL	E DEPTH
PART#	ROUGH OPENING WIDTH*	OPENING		WITH NO SETBACK	
REB14	171/8"	15"	75 lbs.	13"	12"
REB18	171/8"	19"	75 lbs.	17"	16"

*Rough opening will be extended by components wider than 17". **Rough opening depth will be extended by components deeper than the stated useable depth.





The ASR Series Slide Out Rotating System is ideal for smaller systems and has a useable depth of 16-1/8". This system is available in four sizes with a weight capacity of up to 200 lbs. This product ships ready-to-assemble to reduce shipping costs.

PART#	OVERALL HEIGHT	WEIGHT CAPACITY	# OF SHELVES
ASR-48	47-7/8"	200 lbs.	7
ASR-42	41-7/8"	200 lbs.	6
ASR-36	35-7/8"	100 lbs.	5
ASR-30	29-7/8"	100 lbs.	4



ASR Series economical choice, perfect for use with closed door cabinets



The ASR-HD Heavy Duty Slide Out Rotating System

provides the aesthetics of shelving with customizable shelf fronts. The ASR-HD system has a 19" useable depth and is available in three sizes with a weight capacity of up to 250 lbs. This product ships fully assembled to reduce installation time.

PART#	OVERALL HEIGHT	WEIGHT CAPACITY	# OF SHELVES
ASR-60-HD	60"	250 lbs.	9
ASR-42-HD	42"	200 lbs.	6
ASR-30-HD	30"	200 lbs.	4





shelf fronts feature an attractive silver brushed finish and can be replaced to match any finish

		* Installation photo by Electronics Design Group, Inc., Piscataway, NJ
Challenge –	Selecting a free-standing rack that complements any room's décor.	
Solution —	The Slim 5 Series versatile rack frame system satisfies many design requirements and is suited for applications requiring the look of fine furniture.	

The Slim 5 Series Versatile Rack Frame System

is an excellent solution when rear access isn't an issue, or when a permanent installation is not an option. Offered in commonly used sizes ranging from 8 to 43 spaces, our Slim 5 rack enclosures have an overall width of only 19-1/8" and arrive ready-to-assemble to save on shipping.

See pgs. 94-107 of the 2007 Master Catalog	POWER STRIPS*	WEIGHT CAPACITY	OVERALL HEIGHT	RACKING HEIGHT	26" USEABLE DEPTH PART #	20" USEABLE DEPTH PART #
for complete list of power products.	N P T	400 lbs.	79"	75-1/4" (43 space)	5-43-26	5-43
1 1	G J N	400 lbs.	68-1/2"	64-3/4" (37 space)	5-37-26	5-37
Requires PB-5A to mount power strip.	E G J	400 lbs.	54-1/2"	50-3/4" (29 space)	5-29-26	5-29
1 1	E G	400 lbs.	40-1/2"	36-3/4" (21 space)	5-21-26	5-21
 Requires PB-XS to mount power strip. 	C 🔳	400 lbs.	28-1/4"	24-1/2" (14 space)	5-14-26	5-14
mount power strip.	C •	400 lbs.	17-3/4"	14" (8 space)	5-8-26	5-8

Wood Side Panels

5-8

mounting solution for use in an equipment room.

The ERK Series welded rack enclosure provides many options for cooling and cable management.

are aesthetically pleasing and are made using genuine oak.

PART #

WSP-5-43-26 5-43-26

WSP-5-37-26 5-37-26

WSP-5-29-26 5-29-26

WSP-5-21-26 5-21-26

WSP-5-14-26 5-14-26

WSP-5-8-26 5-8-26

FITS

Casters can be added to provide mobility.

FOR USE ON

FINE FLOORS

5WR

5WLR

CBS-5R

CBS-5-26R

6 7 7 7 5wr

5W

5WL

CBS-5

CBS-5-26

FOR USE ON

STANDARD FLOORING

Doors, casters and other

1 INVANIAN

Slim 5 shown with optional wood side banels and plexiglass front door

> options are available to finish your installation. Please visit our website or request a full line catalog for more information

Challenge

Solution -

PART # WSP-5-43 WSP-5-37 WSP-5-29 WSP-5-21 WSP-5-14

WSP-5-8

Providing a robust

FITS 5-43 5-37 5-29 5-21 5-14

The ERK Series Welded Rack Enclosure

is an excellent choice when an enclosed rack is desired.

20" OUTSIDE DEPTH (18 ¹⁵ /32" USEABLE) PART #	25" OUTSIDE DEPTH (23 ¹⁵ /32" USEABLE) PART #	RACKING HEIGHT	OVERALL HEIGHT	POWER STRIPS
ERK-4420*	ERK-4425*	77" (44 space)	$81^{1}/_{8}$ "	N P R T
ERK-4020*	ERK-4025*	70" (40 space)	74 ¹ / ₈ "	G N P
ERK-3520*	ERK-3525*	611/4" (35 space)	65 ³ /8"	G J N
ERK-2720*	ERK-2725*	471/2" (27 space)	51 ³ /8"	E G J
ERK-2120*	ERK-2125*	36 ³ / ₄ " (21 space)	407/8"	E G
ERK-1820*	ERK-1825*	311/2" (18 space)	355/8"	CE
*available withou	ut rear door, suffix	part # with LRD'.		



CBS-5

DESCRIPTION

skirted caster base with non-locking

skirted caster base with non-locking

casters, 20" depth models

casters 26" depth models

non-locking

locking

A full line of enclosures is available for dedicated equipment rooms. Please visit our website or request a full line catalog for additional information.

MRK Series Gangable Rack Enclosure



SR Series Pivoting Rack



WR Series Roll Out Rotating System in Steel Host Enclosure



Challenge -

Installing audio and video equipment flush into a wall or cabinet, while maintaining easy access to rear connections.

Solution

Unique pull-out equipment racks provide convenient access to connections (while saving valuable labor time during installation and subsequent service calls!)

* Installation by Home Systems

The Innovative AXS System

allows an entire system to be pulled out for installation and servicing. Designed to be built in to a closet or wall, the AXS system accommodates today's modern audio and video components & provides an appealing flush-mount design complementing any décor.

	PART #*		EXT. LENGTH	FRAME DEPTH	WEIGHT CAPACITY	ROTATING
£.	AXS-xx-26	xx equals # of useable sp. (15 to 43 sp.)	48"	26"	650 lbs.	no
L	AXS	then the # of useable sp. (15 to 43 sp.)	48"	20"	650 lbs.	no
1	AXS-SX	then the # of useable sp. (10 to 43 sp.)	25"	20"	650 lbs.	no
ı.	SAX	then the # of useable sp. (15 to 43 sp.)	48"	16-1/2"	650 lbs.	no
L	SSAX	then the # of useable sp. (10 to 43 sp.)	25"	16-1/2"	650 lbs.	no
	AX-SXR	then the # of useable sp. (15 to 43 sp.)	31"	20"	450 lbs.	yes

Service Tracks & Service Stand required for installing and servicing

Service Tracks - pair of removable service tracks

PART #	USE WITH		RACK FRAME EXT. DEPTH
TRACK50	AXS, SAX	50"	48"
TRACK31	AX-SXR	31"	31"
TRACK25	AX-SX, SSAX	25"	25"

AXS-WT Cable Management Tray

provides additional capacity for large cable bundles. Mounts between cable carriers of any AXS Series slide out rack. Fits all existing AXS systems. Not for use with AX-SXR rotating slide out rack.

The SRSR Rotating Sliding Rail System

Service Stands - removable telescoping stand that supports and levels the service tracks

	HEIGHT RANGE
PART #	OFF THE FLOOR
TS310	3½" to 10"
TS1022	10" to 22"
TS1640	16" to 40"

FITS

AXS, SAX

AXS-WT25 AX-SX, SSAX

extends a full 19" or 23", depending on model, and rotates 90°! Great for in-cabinet mounting,

the innovative SRSR system is available in a variety of sizes and accommodates up to 250 lbs.

Providing enhanced access to rear connections, the unit locks in place at 0°, 60° and 90° positions to ease installation and servicing. Each SRSR rack includes front and rear rackrail, an effective cable management system, locking panel \mathcal{E} hardware.

PART #

AXS-WT50

*Gasket and guide kit provide the finishing touch to your installation, add "-GG" to the part #

brush gasket closes gaps





with brush gasket brush gasket













Locks in the extended position for simplified equipment integration

DESCRIPTION PART # SRSR-2-xx (# of useable 2 slide, spaces, from 12 to 24) 125 lb. capacity 4 slide, 250 lb. capacity SRSR-4-xx (# of useable spaces, from 12 to 30)

Use the SRSR-2-xx or the SRSR-4-xx for

installations where a 19" useable depth

is required, or when a 250 lb. weight

capacity is needed (SRSR-4-xx only).

When a greater depth is needed for components such as the Sony DVP-CX777ES, use the SRSR-X-xx, which boasts a 23" useable depth, 200 lb. weight capacity, and fits into 24" millwork enclosures!

PART # DESCRIPTION SRSR-X-xx (# of useable 4 slide, 200 lb.

spaces, from 12 to 30) capacity











Models also available for <u>use in Eu</u>rope

Component Cooler removes heat right at the source. Optimized for components on open shelving, this cooler turns on a

Optimized for components on open shelving, this cooler turns on automatically when satellite/ cable boxes, receivers and other heat generating components get too hot. Place the component cooler directly on top of vents of equipment. The COMP-COOL-3 is available for systems that require multiple spot-cooling solutions.

PART #	QUANTITY	FREE AIR RATING	MAX SOUND LEVEL
COMP-COOL	1 fan	8 CFM	19 dB
COMP-COOL-3	3 fans, piggybacked to single power supply	8 CFM/Fan	24 dB
COMP-COOL-E	1 fan, piggybacks to COMP-COOL & COMP-COOL-3	8 CFM	19 dB

Cabinet Cooler removes heat generated by components located in smaller cabinets and entertainment centers.

Operating only when needed to minimize dust, this quiet-cooling device features an aesthetically designed vent that can be painted to match the environment.

PART #	FREE AIR RATING	MAX SOUND LEVEL
CAB-COOL	20 CFM	24 dB



Closet Cooler removes heat from equipment racks located in closets.

Larger installations located in closets have greater cooling requirements. The Closet Cooler has been designed to handle the heat produced by a full rack of equipment, and do it quietly. All the homeowner will see are two solid oak vents, which can be stained or painted to match any room's décor. This cooling solution runs only when needed, mounts to closet doors, and is available with an active exhaust and passive intake for closets with gaps, or an active exhaust and active intake for tightly sealed closets.

PART #	DESCRIPTION	FREE AIR RATING	MAX SOUND LEVEL
CLS-COOL1	active exhaust, passive intake	50 CFM	25 dB
CLS-COOL2	active exhaust, active intake	50 CFM	28 dB



provide easily accessible storage. Available in a black brushed and anodized finish to match custom rackshelves for a unified, elegant appearance.

PART #	FITS	RACKIN	G HEIGHT	DEPTH
CD	40 compact discs	7"	(4 space)	5-3/4"
CD-1	6 compact discs	1-3/4"	(1 space)	5-1/2"
LP	laser discs, LP's, binders	14"	(8 space)	12-9/16"
DVD	28 DVD discs	8-3/34"	(5 space)	5-1/2"

Front loading media holders provide quick access to commonly used CDs, DVDs, etc.

DCDPD4, TD4103 compact discsDVDPD4, TD440 DVD discsDVHSPD3, TD324 VHS tapes in reg. case


ACCOMMODATES

Media partitions

PART # FITS

used in our drawers provide

high density media storage.



*UL Listings:

1. UL Standard #1363, relocatable power taps (file #E194316) 2. UL Standard #1363, relocatable power taps (file #E128811)

**Available 11/1/07

Mounts only to the rear of

RSH Series custom rackshelves

Rackmount Power Distribution and Lighting

Available in a variety of configurations for all of your power distribution requirements

Rackmount Power Strips

available in 15 amp, 15 amp sequencing and 20 amp, and utilize one rackspace. Also available with rackmount lighting. All 15 Amp (non-sequencing) power distribution features surge and spike protection and EMI filtering.

PART #	CIRCUITS	# OF OUTLETS	LED LIGHTING*	FINISH
PDLT-815RVA	15 amp (1)	8	yes*	black brushed & anodized
PDLT-815RVC	15 amp (1)	8	yes*	silver brushed & anodized
PD-915R	15 amp (1)	9 (8 rear, 1 front)	no	black powder coat
PD-815RA-PL	15 amp (1)	8	no	black brushed & anodized
PD-815RC-PL	15 amp (1)	8	no	silver brushed & anodized
PD-920R-NS	20amp (1)	9 (8 rear, 1 front)	no	black powder coat
PDS-615R	15 amp (1)	6 individually sequenced	no	black powder coat
LT-1RA	-	-	yes*	black brushed & anodized
LT-1RC	-	-	yes*	silver brushed & anodized

*Also accepts LT-GN gooseneck light for rear illumination

Remote Switchable Power

The MPR series field-configurable modular remote switchable power system is available with 15 amp and 20 amp circuits and can be controlled by a controller from Middle Atlantic Products or any controller that sends dry contact closure, including Crestron® and AMX® systems. Please visit our website or request a full line catalog for more information.



shown with dimmable light extended and lit COMPACT OF STREET, STRE

PD-815SC-PBSH







MPR Series