



## New & Improved - Protects Vulnerable Welding Hoses From Catastrophic Failure

Techflex WELD-WRAP (WWH) is braided from silica yarns with a high temperature coating and as well as hook and loop closure. Commonly used for protecting welding hoses from molten splatter and abrasion from moving and dragging. This product will withstand continuous exposure to temperatures of 500°F, and intermittent exposure to temperatures of 2,000°F.

The heavy duty hook and loop closure ensures a tight seal, and allows Weld-Wrap to be installed easily over existing assemblies. Weld-Wrap also provides a high level of abrasion and penetration protection to increase the useful life of any hoses exposed to rough or abrasive surfaces.

- **Resists Damage from UV, Gasoline, Engine Chemicals, and as Well as Weld Splatter, Hot Slag, and Welding Spark**



| Nominal Size | Part #    | Wall Thickness | Velcro Width | Standard Spool Put-Ups |            | Available Colors | Lbs/100' |
|--------------|-----------|----------------|--------------|------------------------|------------|------------------|----------|
|              |           |                |              | Bulk Spool             | Shop Spool |                  |          |
| 1"           | WWH1.00SV | .051"          | 5/8"         | 50'                    | 25'        | Silver (SV)      | 13.15    |
| 1 1/2"       | WWH1.50SV | .051"          | 5/8"         | 50'                    | 25'        | Silver (SV)      | 16.94    |
| 2"           | WWH2.00SV | .051"          | 5/8"         | 50'                    | 25'        | Silver (SV)      | 20.81    |
| 3"           | WWH3.00SV | .051"          | 5/8"         | 50'                    | 25'        | Silver (SV)      | 28.53    |