


HOOK-UP WIRE



MIL-W-16878/3

TYPE D IRRADIATED



Description:

Stranded Tinned Copper, Irradiated PVC Insulation

Characteristics:

Temperature Rating:

MIL-W-16878: -55°C to +105°C

UL 1431: +105°C

Voltage Rating:

MIL-W-16878

Type D: 1000 Volts

UL Style 1431: 600 Volts

WEICO NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND		
1469	24	7/32	.032	.092
1468	22	7/30	.032	.094
1467	20	19/32	.032	.103
1466	18	19/30	.032	.111
1465	16	19/.0117	.032	.120
1464	14	19/.0147	.032	.134
1463	12	19/.0186	.032	.153
1462	10	37/.0168	.032	.177
1461	8	133/29	.047	.263

WEICO NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND		
1460	6	133/27	.065	.343

COLORS:

0 - Black, 1 - Brown, 2 - Red
 3 - Orange, 4 - Yellow, 5 - Green
 6 - Blue, 7 - Violet, 8 - Gray, 9 - White

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.