


# HOOK-UP WIRE



MIL-W-16878/1

TYPE B IRRADIATED



**Description:**

Stranded Tinned Copper, Irradiated PVC Insulation

**Characteristics:**

Temperature Rating:

MIL-W-16878: -55°C to +105°C

UL 1429: +80°C

Voltage Rating:

MIL-W-16878

Type B: 600 Volts

UL Style 1429: 150 Volts

WEICO NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND		
1428	28	7/36	.010	.035
1426	26	7/34	.010	.038
1424	24	7/32	.010	.043
1424/19	24	19/36	.010	.043
1422	22	7/30	.010	.050
1422/19	22	19/34	.010	.050
1420	20	7/28	.010	.058
1420/19	20	19/32	.010	.058
1418	18	7/26	.010	.068

WEICO NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND		
1418/19	18	19/30	.010	.068
1416/19	16	19/.0117	.010	.077
1414/19 *	14	19/.0147	.012	.095

\* 1414/19 (UL 1534)

**COLORS:**

0 - Black, 1 - Brown, 2 - Red  
3 - Orange, 4 - Yellow, 5 - Green  
6 - Blue, 7 - Violet, 8 - Gray, 9 - White

**STRIPES:**

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

**Standard Put-Ups: 100 ft., 1000 ft.**