


# HOOK-UP WIRE



MIL-W-16878/2

TYPE C IRRADIATED



**Description:**

Stranded Tinned Copper, Irradiated PVC Insulation

**Characteristics:**

Temperature Rating:

MIL-W-16878: -55°C to +105°C

UL 1430: +105°C

Voltage Rating:

MIL-W-16878

Type C: 1000 Volt

UL Style 1430: 300 Volts

WEICO NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND		
1446	24	7/32	.016	.058
1446/19	24	19/36	.016	.058
1447	22	7/30	.016	.064
1447/19	22	19/34	.016	.064
1448	20	7/28	.016	.072
1448/19	20	19/32	.016	.072
1449	18	7/26	.016	.082
1449/19	18	19/30	.016	.082
1450	16	19/.0117	.016	.091

WEICO NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND		
1451 *	14	19/.0147	.016	.105
1452 *	12	19/.0186	.016	.124

\* 1451 & 1452 (UL 3317)

**COLORS:**

**0** - Black, **1** - Brown, **2** - Red  
**3** - Orange, **4** - Yellow, **5** - Green  
**6** - Blue, **7** - Violet, **8** - Gray, **9** - White

**STRIPES:**

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

**Standard Put-Ups: 1000 ft.**