

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: **XHHW-14-1004**
Description: 14 AWG (2.08MM2) XHHW-2 90 DEGC DRY, 75
DEGC WET XLPE INSULATED 600V, 19 STRANDS
TINNED

Conductor (Stranding): 19 X .0147" Tinned Copper, UL

Conductor OD (Nom) 0.073 inches
Max. Lay Length: 2.0 inch Lay
Min Avg Wall Thickness: 0.030 inches
Nom. O. D: 0.166 inches
Min. O. D: 0.163 inches
Circular Mils (CMA): 4028 (Min)
Strip Force 5 lbs (min) - 20 lbs (max)

Surface Print: 14 AWG (2.08 MM2) (UL) XHHW-2 600V E7088 CSA
TYPE RW90 600V FT1 LL55996

This product is RoHS Compliant

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
Packard: N/A	Other: UL / CSA SUB 44	

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)

Date: 6-20-2012
Mat'l Spec Form (#F-0270)

Rev. 0

7-30-1998