

1.0 **Wire Description**

1.1 **Physical Characteristics**

- 1.1.1 Temperature Range -40°C to 150°C
- 1.1.2 Voltage Rating 60 V

1.2 **Conductor**

- 1.2.1 Conductor Material Copper – Tin Plated
- 1.2.2 Size 0.50 mm²
- 1.2.3 Construction 19/0.19
- 1.2.4 Nominal Diameter 0.91 mm
- 1.2.5 Maximum DC Resistance 36.2 mΩ/M @ 20°C

1.3 **Insulation**

- 1.3.1 Insulation Material Crossed Linked Fluoroelastomer, J7
- 1.3.2 Color Red
- 1.3.3 Wall Thickness 0.28 mm Min
 0.40 mm Nom
- 1.3.4 Nominal Diameter 1.73 mm
- 1.3.5 OD Tolerance ± 0.076 mm
- 1.3.6 Marking None

1.4 **GM Compliance Requirements**

- 1.4.1 GMW15626 Class D
- 1.4.2 GM SOR – Low Voltage Cable For In Transmission Application, Appendix C

1.5 **Reference Specifications**

- 1.5.1 Judd Wire Inc. JW1342-10

ORIGINAL DCR NO. B7854	HAMLIN	PROPRIETARY NOTE: THE INFORMATION ON THIS DRAWING IS THE CONFIDENTIAL PROPERTY OF HAMLIN. THIS DRAWING MUST NOT BE MADE PUBLIC OR COPIED UNLESS AUTHORIZED IN WRITING BY HAMLIN. THIS DRAWING IS SUBJECT TO RETURN UPON DEMAND.	SHEET 1 of 1	DCR No. B8784	REV. AB
DRAWN BY: KPO	DATE: 2011-05-03	DESCRIPTION OF REVISION: Corrected for typo (1.2.3 Construction)	DRAWN BY: GEB	DATE: 2012-06-06	
APP'D BY: KPO	DATE: 2011-05-26		APP'D BY: GEB	DATE: 2012-06-07	