



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA36A3N131TD12E  
 7818102902933  
 ALLUG-600KCM-NEMA-NARTNG  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Length (in) 5.71  
 Bolt Hole Size (in) 0.52  
 Thickness 0.39  
 B Length (in) 1.64  
 Pad Width (in) 1.31  
 E - in 1.75  
 Strip Length 1-11/16

**General**

Number of Holes 2  
 Product Description Cu & Al Compression terminal, 2 Holes/W/insp W, 250-600 kcmil, 600V-35Kv, 1/2" stud, Pink, 300 Index, Narrow tongue terminal

**Conductor(s)**

Flex (Class G) Size - Range N/A  
 Flex (Class H) Size - Range N/A  
 Flex (Class I) Size - Range N/A  
 Copper Solid Size (Range) N/A  
 DLO Size (Range) N/A  
 Copper Stranded (Range) 600 kcmil

**Physical**

Type of Plating Tin - Electro Plated  
 Bolt Hole Size 1/2  
 Color Code Pink  
 Plated (Yes or No) Y  
 Index Number 300  
 Product Material Aluminum

**Approvals / Certifications**

UL Listed Y  
 CSA Certified Y  
 ROHS Compatible Compliant  
 UL Recognized N  
 CULUS N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175